



NOTES

If the top of the underfloor heating pipes is to be less than 50mm from the F.F.L., the following applies:

For each of the 14no floor socket locations, a 300 x 300mm square area should be left clear of underfloor heating pipes.

E: RC CSP2-2027 11/1/06 NOTE UPDATED.
 D: IW, 12/11/04, CSP2-1928. TWO FLOOR SOCKETS ADDED TO ALLOW FIXING OF ADJ' POLE FRAME No.8
 C: TJH, 17-09-04, CSP2-1897. 175mm DIMENSION OMITTED DUE TO THAT PROJECTION BRACKET NOT BEING MANUFACTURED.
 B: TJH, 24-11-03, CSP2-1784. ALL DIMENSIONS RECHECKED AND AMENDED WHERE APPROPRIATE.
 A: TJH, 25-09-01, CSP2-1549. RE DRAWN ON CAD SHOWING MORE DETAILS.



Tel:Huddersfield(01484)542051 Fax:(01484)539148

**STEEL FOLDAWAY CLIMBING FRAME (THREE GATES),
 Floor socket locations.**

scale	date	dr	rev
NTS	25/09/01	TJH	E

dwg no **448-07**

LOCATION PLAN

This drawing is to be read in conjunction with dwg 420-41