



REPEAT DIMENSIONS THIS SIDE AS SHOWN OPPOSITE

FRAME CAN BE FOLDED EITHER SIDE

ADDITIONAL FOOT SHOOT BOLT PLATES FOR ADJ' POLE FRAME No.8

LOCATION PLAN

This drawing is to be read in conjunction with dwg 420-41

NOTES

If the top of the underfloor heating pipes are within 50mm of the F.F.L., the following applies:

For each of the 14no floor socket locations, a 300 x 300mm square area should be left clear of underfloor heating pipes.

* The 225mm dimension shown on this drawing is on the basis that no projections / obstructions (radiators, whiteboards, trunking etc) will effect the frames folding back against the wall. If you have any issues please contact us to discuss further.

F: RC CSP2-2284 26/7/12. MIN PIVOT DIM SHOWN ONLY. NO OBSTRUCTIONS NOTE ALSO ADDED TO DRAWING.
 E: RC CSP2-2027 11/1/06 NOTE UPDATED.
 D: IW, 12/11/04, CSP2-1928. TWO FLOOR SOCKETS ADDED TO ALLOW FIXING OF ADJ' POLE FRAME No.8
 C: TJH, 17-09-04, CSP2-1897. 175mm DIMENSION OMITTED. DUE TO THAT PROJECTION BRACKET NOT BEING MANUFACTURED.
 B: TJH, 24-11-03, CSP2-1784. ALL DIMENSIONS RECHECKED AND AMENDED WHERE APPROPRIATE.
 A: TJH, 25-09-01, CSP2-1549. RE DRAWN ON CAD SHOWING MORE DETAILS.



Tel:Huddersfield(01484)542051 Fax:(01484)539148

STEEL FOLDAWAY CLIMBING FRAME (THREE GATES), Floor socket locations.

scale	date	dr	rev
1:20	25/09/01	TJH	F

dwg no **448-07**