



FORWARD FOLDING

REARWARD FOLDING

Notes

Suitable support steel work should be provided approximately 6.0 metres either in front or behind, the front face of the basketball board in the play position. The steel work installed must be capable of accepting a 350 kgs deadweight at any point along it's length and two sections of steel at 1.2 metres centres are necessary.

G: JC CSP2-2246 11/10/10. 350KG SWL CHANGED TO DEADWEIGHT DUE TO THE TERMINOLOGY BEING MISLEADING.
 F: RC 28/9/06 CSP2-2072. MINOR CHANGES & NOTES ADDED.
 E: TJH, 07-01-04, CSP2-1796. DIMENSION 565mm DIMENSION WAS 700mm.
 D: TJH, 29/10/01, CSP2-1556. DRAWING HAS BEEN CHANGED FROM A TRACK WAY SUSPENDED MATCH PLAY BASKETBALL GOAL, TO ELECTRICALLY OPERATED REARWARD/FORWARD FOLDING BASKETBALL GOALS.
 C: TJH, 11/01/01, CSP2-1477. REDRAWN ON C.A.D. WITH MINOR UPDATED CHANGES.



Tel:Huddersfield(01484)542051 Fax:(01484)539148

SPORTS HALL, ELECTRIC WINCH OPERATED REARWARD/FORWARD FOLDING BASKETBALL GOALS.

scale	date	dr	rev
1:50	29/10/01	T.J.H.	G

dwg no **SH-10**