



NOTES

We provide a timber wallpad, 3660 x 95 x 45mm which is positioned horizontally at any height to suit the wall conditions.

The wallpad is best secured with 7No M10 50L rawlbolts, but depending on the structure it can be fixed with coachscrews or drilling and tapping for bolts.

The wallpad bracket as detailed on dwg No WHCF-08 is held with 4No 8mm dia x 45mm long coachscrews.

The frame bracket as detailed on dwg No WHCF-08 which is fixed with 4No No12 x 32mm long c/sk headscrews acts as the hinge. The floor pivot bracket locates in to the same centre line as the bracket above.

The tension clamp housings are each fixed with 3No countersunk head woodscrews to 560 x 95 x 45mm timber wallpads each twice rawlbolted to the wall.

The locking bracket is fixed with 2No 8mm dia x 45mm coachscrews to the main timber wallpad

B: PJ CSP2-2214, 02/11/09. OUTLINE OF CLIMBING FRAME ADDED.
A: NGK CSP2-1738, 04/06/03, DRAWN UP ON CAD.



Continental Sports Limited
Paddock, Huddersfield HD1 4SD
Tel: Huddersfield (01484) 542051 Fax: (01484) 539148
Website: <http://www.contisports.co.uk>
E-Mail: sales@contisports.co.uk

**WALL HINGED CLIMBING FRAMES
INSTALLATION DETAILS FOR A
PAIR OF FRAMES FOLDING OVER
ONE ANOTHER.**

scale	date	dr	rev
1:20	04/06/03	NGK	B
projection	dwg no		
	WHCF-09 SH4		